

SANDIA REPORT

SAND2014-XXXX
Unlimited Release
December 2014

IDC Reengineering Phase 2 Glossary

Version 1.0

Christopher J. Young, James Mark Harris

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.

Approved for public release; further dissemination unlimited.



Sandia National Laboratories

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831

Telephone: (865) 576-8401
Facsimile: (865) 576-5728
E-Mail: reports@adonis.osti.gov
Online ordering: <http://www.osti.gov/bridge>

Available to the public from
U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Rd.
Springfield, VA 22161

Telephone: (800) 553-6847
Facsimile: (703) 605-6900
E-Mail: orders@ntis.fedworld.gov
Online order: <http://www.ntis.gov/help/ordermethods.asp?loc=7-4-0#online>



SAND2014-XXXX
Unlimited Release
December 2014

IDC Reengineering Phase 2 Glossary

Christopher J. Young, James Mark Harris
Next Generation Monitoring Systems Department
Sandia National Laboratories
P.O. Box 5800
Albuquerque, New Mexico 87185-MS0401

Abstract

This document contains the glossary of terms used for the IDC Reengineering Phase 2 project. This version was created for Iteration I2.

REVISIONS

Version	Date	Author/Team	Revision Description	Authorized by
0.1	7/31/2014	SNL IDC Reengineering Team	Initial Release for I1	M. Harris
1.0	12/15/2014	SNL IDC Reengineering Team	Release for I2	M. Harris

TABLE OF CONTENTS

Revisions	4
1 Terms	10
1.1 Active Review	10
1.2 Aftershock Sequence	10
1.3 Agglomerative Hierarchical Clustering	10
1.4 Alphanumeric Data	10
1.5 Alphanumeric List	10
1.6 ALT (Alternate Subsystem)	10
1.7 Amplitude Correction Factor	10
1.8 Analysis Time Interval	11
1.9 Area of Interest	11
1.10 Array	11
1.11 Array Coherence	11
1.12 Aseismic Region	11
1.13 Association	11
1.14 Attenuation	11
1.15 Automatic Processing	11
1.16 Azimuth	12
1.17 Backup	12
1.18 Basemodel	12
1.19 Beam	12
1.20 Beam Steering	12
1.21 Beam, Coherent	12
1.22 Beam, Continuous	12
1.23 Beam, Detection	12
1.24 Beam, fk	13
1.25 Beam, Incoherent	13
1.26 Beam, Origin	13
1.27 Beam, Virtual Origin	13
1.28 Beamforming (Beaming)	13
1.29 Beamforming (Beaming), Coherent	13
1.30 Beamforming (Beaming), Incoherent	14
1.31 CD-1.0 Format and Protocols	14
1.32 CD-1.1 Format and Protocols	14
1.33 Cepstral Domain Measurements	14
1.34 Channel	14
1.35 Channel, Derived	14
1.36 Channel, Raw	15
1.37 Compensated Linear Vector Dipole	15
1.38 Correlation Coefficient	15
1.39 CSS 3.0 Format	15
1.40 Data Acquisition	15
1.41 Data Acquisition Partition	15

1.42	Data Authentication	15
1.43	Data Processing Partition	15
1.44	Data Provider	16
1.45	Data Quality Errors	16
1.46	Data Source	16
1.47	Database Backup	16
1.48	Database Restore	16
1.49	Defining/Non-Defining	16
1.50	Deviatoric Component (of Moment Tensor)	16
1.51	Double Couple Component (of Moment Tensor)	16
1.52	Earth Model	17
1.53	Earth Model, 1D	17
1.54	Earth Model, 2D	17
1.55	Earth Model, 3D	17
1.56	Empirically Derived Corrections	17
1.57	Event	17
1.58	Event Bulletin	18
1.59	Event Change History	18
1.60	Event Epicenter	18
1.61	Event Hypocenter	18
1.62	Event Hypothesis	18
1.63	Event Hypothesis Location Solution	18
1.64	Event Hypothesis Quality Metric	18
1.65	Event Location	18
1.66	Event Magnitude, Network	18
1.67	Event Magnitude, Station	19
1.68	Event Quality Metric	19
1.69	Event Report	19
1.70	Event Set	19
1.71	Event Signal Detection Template	19
1.72	Expected Signal Detection	19
1.73	False Event	20
1.74	Filter Cascade	20
1.75	Filter, Waveform	20
1.76	Focal Mechanism	20
1.77	Focal Sphere Plot	20
1.78	Frequency Domain Measurements	20
1.79	Frequency-Wavenumber (fk) Measurements	20
1.80	Frequency-Wavenumber (fk) Power Spectrum	21
1.81	Frequency-Wavenumber (fk) Processing	21
1.82	F-statistic	21
1.83	Geographic Data	21
1.84	Geographic Information System (GIS)	21
1.85	Geometric Spreading	21
1.86	Geospatial Data	21
1.87	Green's Function	22

1.88	GSE 2.1/IMS 1.0 Formats and Protocols.....	22
1.89	Historical Data.....	22
1.90	Hydroacoustic Arrival Group (HAG).....	22
1.91	Hydroacoustic Time Domain Measurements.....	22
1.92	IDC (International Data Center).....	22
1.93	IMS (International Monitoring System).....	22
1.94	Interactive Processing.....	23
1.95	IRIS-DMC.....	23
1.96	Isotropic Component (of Moment Tensor).....	23
1.97	Late Signal Association.....	23
1.98	Late-Arriving Waveform.....	23
1.99	Machine Readable Earthquake Data Report.....	23
1.100	Magnitude Estimation.....	23
1.101	Magnitude Type.....	24
1.102	Master Event Relocation.....	24
1.103	Maximum Likelihood Magnitude Estimation (MLE).....	24
1.104	Mini-SEED Format.....	24
1.105	Missed Event.....	24
1.106	Mission Transfer.....	24
1.107	Moment.....	24
1.108	Moment Tensor.....	25
1.109	Moment Tensor Inversion.....	25
1.110	Monitoring Mission Performance.....	25
1.111	Near Real Time.....	25
1.112	Network.....	25
1.113	Network Magnitude Detection Threshold.....	25
1.114	Network Processing.....	25
1.115	Noise.....	26
1.116	Operational Processing Time Period.....	26
1.117	Operational Subsystem.....	26
1.118	Operations Log.....	26
1.119	OPS (Operational Subsystem).....	26
1.120	Origin.....	26
1.121	Phase.....	26
1.122	Phase Grouping.....	26
1.123	Pipeline Processing.....	26
1.124	Pipeline Transfer.....	27
1.125	Pixel Family.....	27
1.126	PKI (Public Key Infrastructure).....	27
1.127	PKI Credentials.....	27
1.128	Playback.....	27
1.129	Polarization Features.....	27
1.130	Power Detector.....	27
1.131	Preliminary Phase Label.....	27
1.132	Primary.....	28
1.133	Processing Sequence.....	28

1.134 Processing Stage.....	28
1.135 Processing Unit.....	28
1.136 Progressive Multi-Channel Correlation (PMCC).....	28
1.137 Q (Quality Factor)	29
1.138 QC Mask.....	29
1.139 QuakeML	29
1.140 Quality Control (QC).....	29
1.141 Radiation Pattern	29
1.142 Reference Event.....	29
1.143 Reference Event Database.....	29
1.144 Regression Testing	29
1.145 Rejected Event Hypothesis	29
1.146 Relative Event Magnitude Estimation	30
1.147 Relative Event Relocation.....	30
1.148 Remote Operations Center (ROC).....	30
1.149 Rotation.....	30
1.150 SEED Format	30
1.151 Sensor Orientation	30
1.152 Signal	30
1.153 Signal Association	31
1.154 Signal Characterization.....	31
1.155 Signal Detection	31
1.156 Signal Detection Feature.....	31
1.157 Signal Detection Feature Measurement.....	31
1.158 Signal Detection Feature Prediction	31
1.159 Signal Detection Template.....	31
1.160 Signal Detector Threshold	31
1.161 Signal Enhancement	32
1.162 Signal of Interest.....	32
1.163 Single-Station Event Hypothesis.....	32
1.164 Site	32
1.165 Slowness.....	32
1.166 Source Type.....	32
1.167 Source Type Plot	32
1.168 STA/LTA	32
1.169 Standalone Subsystem	33
1.170 Station	33
1.171 Station Data.....	33
1.172 Station Magnitude.....	33
1.173 Station Magnitude Detection Threshold.....	33
1.174 Station Processing.....	33
1.175 Station State-Of-Health (SOH)	33
1.176 Storage Format	34
1.177 Subspace Detector	34
1.178 Swarm Sequence	34
1.179 System Backup.....	34

1.180 System Configuration	34
1.181 System Message	34
1.182 System Performance	34
1.183 System Restore	35
1.184 System Storage Format	35
1.185 Test Data Set	35
1.186 Three Component Station	35
1.187 Time Domain Measurements	35
1.188 Training Data Set.....	35
1.189 Training Subsystem	35
1.190 Unit Testing.....	35
1.191 Virtual Event Hypothesis	36
1.192 Virtual Origin	36
1.193 Waveform.....	36
1.194 Waveform Correlation Event Processing.....	36
1.195 Waveform Processing	36
1.196 Waveform QC Mask.....	36
1.197 Waveform Quality Control	36
1.198 Waveform, Derived	36
1.199 Waveform, Raw.....	37

1 TERMS

1.1 Active Review

The state of a set of data indicating an Analyst is reviewing the data. The set of data in Active Review is defined by either an event being refined and its associated signal detections and waveforms, or the time interval of visible waveforms and signal detections being scanned. The system prevents changes by automated processing to data in Active Review. Analysts are notified of relevant data in Active Review by other analysts.

1.2 Aftershock Sequence

A set of smaller events following a large earthquake (the mainshock) that are caused by the Earth adjusting to the new state of stress on the main fault and surrounding medium. Aftershocks occur within the spatial extent of the mainshock fault rupture and have similar source mechanisms. The overall trend is for aftershocks to decrease in frequency and size with time after the mainshock. An aftershock sequence can last days, weeks, or months depending on the size of the mainshock.

1.3 Agglomerative Hierarchical Clustering

A method to find clusters of similar individuals within a population. The population is the set of waveforms recorded at a single station for a set of events and the measure of similarity is correlation coefficient. Agglomerative hierarchical clustering iteratively clusters waveforms into a single tree-like structure called a dendrogram. For more information on the agglomerative hierarchical clustering algorithm, see the book Cluster Analysis, by Everitt et al.

1.4 Alphanumeric Data

Data that is displayed to an analyst as numbers or letters, e.g. the latitude and longitude of an event hypothesis. This is in contrast to waveform data.

1.5 Alphanumeric List

Alphanumeric data presented in a multi-column table. A list of events, a list of signal detections for an event, or a list of stations are all examples.

1.6 ALT (Alternate Subsystem)

A duplicate of the Operational Subsystem (OPS) software and hardware at a geographically separate location. The ALT is continuously available to assume mission responsibilities.

1.7 Amplitude Correction Factor

A phase and frequency specific multiplicative factor which represents the decrease in the amplitude of a wavefront due to attenuation as it travels from source to receiver. Amplitude correction factors are applied in conjunction with corrections due to geometric spreading.

1.8 Analysis Time Interval

The time interval bounding the data reviewed by an analyst. That data includes waveforms, event hypotheses and their associated signal detections, and unassociated signal detections.

1.9 Area of Interest

A geographic region deemed to be important for the operational monitoring mission.

1.10 Array

A group of stations (sometimes referred to as "elements") deployed with the intent of processing waveform data with specialized techniques exploiting signal coherence between the stations. This processing improves SNR and also provides estimates of the direction (azimuth and slowness /velocity) of signals. Arrays are used for seismic, infrasonic, and hydroacoustic monitoring.

1.11 Array Coherence

A measure of the similarity of waveforms during a given time interval between the elements of an array. High array coherence indicates that a signal is propagating across the array.

1.12 Aseismic Region

A region of the Earth where no seismic events have ever been recorded. Many seismic monitoring techniques (e.g. magnitude estimation, estimating station magnitude detection threshold, waveform correlation event processing) leverage results from past events, so aseismic regions present additional challenges.

1.13 Association

See signal association.

1.14 Attenuation

The decrease in amplitude of a signal due to loss of energy as the signal propagates away from its source. Attenuation consists of two components: intrinsic attenuation which is the phenomenon in which kinetic energy is converted to heat by anelastic processes or internal friction, and scattering attenuation, which is caused by energy reflecting off of small scale material heterogeneities. In addition to attenuation, geometric spreading also acts to modify the amplitude of seismic signals.

1.15 Automatic Processing

Data processing that is performed by the system without analyst interaction. This type of processing is initiated by a configurable trigger such as availability of data or the completion of a

previous processing step. Includes station processing, network processing, post-analysis processing, post-evaluation processing, and late data processing.

1.16 Azimuth

The angle in degrees measured clockwise from geographic North of a signal arriving at a station. Azimuth and slowness completely describe the vector direction of arrival for a signal at a station.

1.17 Backup

The Subsystem acting as the backup location for the System. The pipeline and analyst processing do not actively run on the Backup. May be either OPS Subsystem or ALT Subsystem. The Primary always synchronizes data to the Backup. During a pipeline transfer, the Primary and Backup roles switch.

1.18 Basemodel

An Earth model used to compute base-level predictions (e.g. seismic travel time) that can be made more accurate by applying empirically derived corrections developed specifically for that basemodel. An Earth model is only referred to as a basemodel when predictions are further refined using empirically derived corrections.

1.19 Beam

The product of beamforming ; a single derived channel (see channel, derived) representing the sum of the raw channels (see channel, raw) for all the elements of an array.

1.20 Beam Steering

See beamforming.

1.21 Beam, Coherent

The derived channel (see channel, derived) resulting from coherent beamforming (see beamforming, coherent).

1.22 Beam, Continuous

A beam channel formed continuously in time, i.e., without any specified start or end time.

1.23 Beam, Detection

The beam on which a signal detection occurs. When detecting signals for data from an array, a set of beams is formed spanning the regions of monitoring interest. Detectors are run on all of these beams to look for signals. If a signal is detected, the beam on which the detection occurred is known as the detection beam. If there are detections on more than one beam, then the best of these will be selected (e.g. best SNR) as the detection beam.

1.24 Beam, fk

A beam steered to point to the maximum fk power spectrum direction (azimuth and slowness) in 2D fk space (see frequency wavenumber processing) corresponding to a signal detection on an array. The fk beam should show the best possible signal for a signal detection and hence is the beam that is automatically shown to an analyst reviewing an event hypothesis.

1.25 Beam, Incoherent

The derived channel (see channel, derived) resulting from incoherent beamforming (see beamforming, incoherent).

1.26 Beam, Origin

A beam steered to the location of an event hypothesis. A particular phase (typically first arriving P) must be assumed for each origin beam. When an event hypothesis is displayed for an analyst to review, fk beams are shown for detecting stations, and origin beams are shown for non-detecting stations. Assuming the Event hypothesis is well-located, the origin beams should allow the analyst to manually add any signal detections that were missed.

1.27 Beam, Virtual Origin

A continuous beam (see beam, continuous) steered to a virtual origin location. Virtual origin beams are used to monitor focused areas of interest for long periods of time, e.g. known test sites.

1.28 Beamforming (Beaming)

Beamforming (also known as beaming) is a multichannel signal processing technique taking advantage of the direction-dependent arrival of a signal across an the elements of an array. Beamforming sums the waveform data from the elements of an array to produce a single derived channel (see channel, derived). The intent is to boost SNR.

1.29 Beamforming (Beaming), Coherent

A method for increasing the SNR of signals arriving at an array from a particular azimuth and slowness. Coherent beamforming (also known as beam steering) time shifts the waveforms from an array's elements before summing under the assumption that a plane wave is arriving from that direction. The shifting is done for each element by subtracting the time delay relative to the array beampoint (a reference location for the array) that would be expected for a plane wave arriving from that azimuth and slowness. If there is a signal arriving from the specified azimuth and slowness, an SNR gain occurs when summing the time delayed waveforms due to the simultaneous constructive interference of coherent directional signals and destructive interference of incoherent background noise. In theory, a gain of SNR equal to the square root of the number of elements can be achieved, e.g. a factor of 3 for a 9 element array. In practice, the realized gain is usually less.

1.30 Beamforming (Beaming), Incoherent

The same as coherent beamforming except that the waveforms are rectified (absolute values) before summing.

1.31 CD-1.0 Format and Protocols

A standard used for transmitting continuous waveform data from stations of the International Monitoring System (see IMS) to the International Data Center (see IDC) and for transmitting these data from the IDC to National Data Centers (NDCs). CD-1.0 uses a TCP/IP program-to-program socket communication to send binary formatted waveform data (frames). The CD-1.0 standard has been superseded by the CD-1.1 standard (see CD-1.1 Format and Protocols). The format and protocols are described in the document Formats and Protocols for Continuous Data CD-1.0 from the CTBTO found at ctbto.org/fileadmin/user_upload/procurement/2011/Attachment_3_to_the_TOR.pdf.

1.32 CD-1.1 Format and Protocols

A standard used for transmitting continuous waveform and state-of-health (see SOH) data from stations of the International Monitoring System (see IMS) to the International Data Center (see IDC) and for transmitting these data from the IDC to National Data Centers (NDCs). This protocol is designed to support multicasting of continuous data, which entails more complex data flow topologies. The format and protocols are described in the document Formats and Protocols for Continuous Data CD-1.1 from the CTBTO found at ctbto.org/fileadmin/user_upload/procurement/2011/Attachment_4_to_the_TOR.pdf.

1.33 Cepstral Domain Measurements

Measurements made in the cepstral domain for characterizing a signal of interest, in particular hydroacoustic signals. The cepstral domain highlights periodicities in the spectrum (frequency domain). A cepstrum of a waveform is the Fourier transform of the waveform's power spectrum. The independent variable of the cepstrum is called queffreny, expressed in units of time but representing the period of harmonic features of the waveform.

1.34 Channel

A generic term for either a raw channel (see channel, raw) or a derived channel (see channel, derived). A time interval of data from a channel is a waveform.

1.35 Channel, Derived

A source for time series data created by processing one or more raw channels (see channel, raw). Examples of common types of processing to form derived channels are filtering (see filter, waveform), beaming (see beamforming), and rotation. Derived channels are generally created to enhance the SNR of signals.

1.36 Channel, Raw

A source for unprocessed time series data from a seismic, hydroacoustic, or infrasonic sensor. E.g. the output from a short period, vertical component seismometer.

1.37 Compensated Linear Vector Dipole

The sub-portion of the deviatoric component of the moment tensor remaining after subtraction of the double couple component.

1.38 Correlation Coefficient

A measure of similarity between two waveforms. The absolute value of the correlation coefficient ranges from 0 (no similarity) to 1 (a perfect match). Formally, the correlation coefficient for two entities is the covariance divided by the square root of the product of the variances. For waveforms, this is the cross-correlation of the two waveforms divided by the square root of the product of the auto-correlations.

1.39 CSS 3.0 Format

A schema that was developed by the former Center for Seismic Studies (CSS) in ~1990 to facilitate storage and retrieval of seismic data used for seismic monitoring of test ban treaties. It consists of 21 relations (database tables) that describe parametric data associated with seismic events, including station information. The CSS3.0 Format is described in the document Center for Seismic Studies Database Schema Version 3.0, June 1990, SAIC-90/1235.

1.40 Data Acquisition

Receiving data from a data provider and storing it for subsequent access by the System. Data can be acquired in a variety of formats including CD-1.0, CD-1.1, IMS-1.0, SEED, and miniSEED.

1.41 Data Acquisition Partition

The portion of the System where data is acquired (see data acquisition) and re-distributed.

1.42 Data Authentication

The corroboration that data have not been altered in an unauthorized manner by using such mechanisms as digital signatures, PKI (public key infrastructure), etc.

1.43 Data Processing Partition

The portion of the System where data are processed, analyzed, evaluated, and where data processing products are distributed and archived.

1.44 Data Provider

See data source.

1.45 Data Quality Errors

Errors in waveforms that can lead to problems with processing and analysis. Data quality errors include data gaps, amplitude spikes, repeated amplitude values, linear trends and invalid gain. Prior to signal processing, data is analyzed by quality control (QC) software to identify and record any errors (see QC Mask).

1.46 Data Source

A source of waveform and/or event data for the System. Data sources can be stations (IMS stations) or external data centers (e.g. IRIS-DMC).

1.47 Database Backup

The copying or archiving of the contents and state of database at a particular point in time. The purpose of making a database backup is to provide the information needed for a database restore, should that be necessary.

1.48 Database Restore

The restoration of a database's previous state. To restore a database, a particular database backup must be selected.

1.49 Defining/Non-Defining

Any observation that contributes to the determination of an event attribute is considered to be "defining" for that attribute. The detection of an event, the location of an event (see event location), the magnitude of an event (see event magnitude, network), and the source type assigned to an event are all determined by specific types of defining observations (travel time, azimuth, slowness, amplitude) from one or more phases recorded by one or more stations. If an observation is linked to an event (associated) but does not contribute to the calculation of an event attribute, then it is considered to be non-defining for that attribute.

1.50 Deviatoric Component (of Moment Tensor)

The portion of the moment tensor remaining after subtraction of the isotropic component. The moment tensor for an idealized earthquake has only a deviatoric component.

1.51 Double Couple Component (of Moment Tensor)

The sub-portion of the deviatoric component of the moment tensor that represents two paired but opposing force couples.

1.52 Earth Model

A representation of one or more physical properties of the Earth, generally used for determining or validating some aspect of an event hypothesis (e.g. signal travel times, signal azimuths, signal slownesses).

1.53 Earth Model, 1D

An Earth model in which the physical properties represented vary only with one dimension. Generally this dimension is depth for seismic and hydroacoustic models and elevation for infrasonic models. 1D depth/altitude varying models are effective because gradients of physical properties are generally much stronger in the vertical direction due to gravitational effects on the solid Earth, oceans, and atmosphere.

1.54 Earth Model, 2D

An Earth model in which the physical properties represented vary with two dimensions. Generally these dimensions are latitude and longitude. There are not many examples of physical properties that vary only with latitude and longitude and not with depth, so 2D models are less common than 1D or 3D models. Examples of types of 2D models are surface wave group velocities (for predicting dispersion) and body or surface wave attenuation (for predicting amplitude).

1.55 Earth Model, 3D

An Earth model in which the physical properties represented vary with three dimensions. Generally these dimensions are latitude, longitude, and depth. 3D Earth models represent the highest level of fidelity of static (non-time varying) Earth models.

1.56 Empirically Derived Corrections

Corrections that are applied to predictions (e.g. seismic travel time) calculated using basemodels to improve fidelity of the predictions. Empirically derived corrections are based on measurements from ground-truth events and are developed specifically for a particular basemodel. Empirically derived corrections are only used by entities that have a need for accuracy beyond what can be provided by an Earth model.

1.57 Event

The occurrence of some source of energy within the Earth's body, oceans, or atmosphere that can be detected by seismic, hydroacoustic, and/or infrasonic sensors. For the same event, many different event hypotheses may be created at different processing stages. One of these event hypotheses must be designated as preferred.

1.58 Event Bulletin

A list of event hypothesis location solutions, with or without the associated signal detections. The primary product of most seismic monitoring agencies (e.g. IDC, NEIC) is an event bulletin. Event bulletins can be constrained by region, by time, by magnitude, etc.

1.59 Event Change History

A complete record of the evolution of the event hypotheses corresponding to a single event, from the initial detection of the event through the final version approved for release.

1.60 Event Epicenter

An event's 2D geographic location as described by latitude and longitude, i.e. the position on a map. This is in contrast to an event hypocenter, which refers to latitude, longitude, and depth.

1.61 Event Hypocenter

An event's 3D spatial location as described by latitude, longitude, and depth. This is in contrast to an event epicenter, which refers only to the latitude and longitude, i.e. the position on a map.

1.62 Event Hypothesis

A set of signal detections and calculated event parameters that are associated with an event. An event hypothesis has one or more event hypothesis location solutions, one of which must be designated as preferred.

1.63 Event Hypothesis Location Solution

An estimate of an event location tied to a particular event hypothesis. Another term for an event hypothesis location solution is an origin.

1.64 Event Hypothesis Quality Metric

See event quality metric.

1.65 Event Location

The combination of an event's spatial location (see event hypocenter), temporal location, spatial location uncertainty, and temporal location uncertainty.

1.66 Event Magnitude, Network

An estimate of the size of a seismic event determined by combining the set of available station event magnitudes (see event magnitude, station). Separate network event magnitudes can be calculated for each available station magnitude type, e.g. mb, Ms.

1.67 Event Magnitude, Station

An estimate of the size of a seismic event determined by processing the waveform data recorded by one station. Separate station event magnitudes can be calculated for different magnitude types, e.g. mb, Ms.

1.68 Event Quality Metric

A quality metric computed as a number in the closed interval [0.0, 1.0] (low to high) for each event hypothesis formed on the System. This metric indicates the quality of the event hypothesis as a function of the event hypothesis' associated signal detections and related measurements, location solution, station state-of-health, and network state-of-health information. The System computes a new event quality metric whenever any parameter used for calculating the metric is updated and stored.

1.69 Event Report

An automatically or manually prepared document providing detailed information about a particular event. Could include text, tables, figures, maps.

1.70 Event Set

The set of one or more event hypotheses that an analyst selects for analysis.

1.71 Event Signal Detection Template

The expected sequence of signal detections associated with a particular size event from a particular area. The template consists of a series of signal detection markers with the correct relative timing that can be superimposed over the waveform display and time shifted to align with observed signals. Detection of a set of signals that match an event signal detection template is an indication that a new event has occurred at a similar location. These templates can be particularly helpful when trying to build events in an aftershock sequence or a swarm sequence.

1.72 Expected Signal Detection

A signal detection that is anticipated to exist but has not been detected by the System. Expected signal detections are typically acquired from empirical knowledge. An Expected Signal Detection is associated with a station, a phase label and an event hypothesis, and may include an expected waveform and/or a set of signal detection feature measurements. It may also contain information about parameters that were used in the past to detect the signal, such as filter settings, fk parameters, etc. An expected signal detection cannot become an observed signal detection directly, but can guide the processes that search waveform data for observed signal detections.

1.73 False Event

An event detected by the System that does not actually correspond to a real source of energy, i.e. an artifact of the data processing. Adjustments can be made to the system to reduce the number of false events, but usually only with a corresponding increase in the number of missed events built by the system.

1.74 Filter Cascade

The application of two or more waveform filters (see filter, waveform) in series. Complex filters can be designed to meet a set of specific needs by applying a series of simple filters, each of which is designed to meet a more basic need. Once the sequence of filters is known, the successive filter operations can be replaced with a single filter operation equivalent to the filter cascade.

1.75 Filter, Waveform

An algorithm that operates on a waveform to produce a second waveform with a limited portion of the original frequency content. Typical waveform filters are low-pass, high-pass, or band-pass. Waveform filters are usually applied to enhance signals relative to noise.

1.76 Focal Mechanism

A representation of the deformation in the source region of a seismic event. The focal mechanism is diagnostic of the type of event (earthquake or explosion).

1.77 Focal Sphere Plot

A plot of the focal mechanism for a seismic event that emphasizes the direction of motion of the P wavefront (away from or towards the event). Focal sphere plots are sometimes referred to as “beach ball” plots. In the case of an earthquake, the focal sphere plot makes evident the orientation and displacement of the fault.

1.78 Frequency Domain Measurements

Measurements made in the frequency domain for characterizing a signal of interest, including: total energy, total power, average power, power spectral density, and signal cepstrum. A segment of waveform data (a time-series) is transformed to the frequency domain using a Fourier transform.

1.79 Frequency-Wavenumber (fk) Measurements

Measurements made from the fk transformed data (see frequency-wavenumber processing) of an array : azimuth, azimuth uncertainty, slowness, slowness uncertainty, and array coherence.

1.80 Frequency-Wavenumber (fk) Power Spectrum

The representation in the frequency-wavenumber domain of coherent signal power in the waveform data from an array for a specified time interval. Calculation of fk power spectrum requires three Fourier transforms to convert time-sampling to frequency (designated by f), and longitude and latitude sampling to x and y wavenumbers (designated by k). Typically fk power spectra are represented as 2D plots (not 3D), by collapsing the frequency information to a single value for each x and y slowness by averaging values across the range of frequencies.

1.81 Frequency-Wavenumber (fk) Processing

A signal processing technique that can be applied to a short interval of waveform data from an array to determine if a signal is present and estimate the signal's azimuth and slowness. Waveform data are first converted to a frequency-wavenumber power spectrum and then further processing is done in the fk domain.

1.82 F-statistic

The power on a beam divided by the average computed over all the array elements of each element's residual power. The F-statistic can be used as the basis for a signal detector for data from an array or to characterize the coherence of the signal detection on a particular beam. Because each point in a frequency-wavenumber (fk) power spectrum corresponds to an azimuth and slowness pair, calculating an F-statistic for each point in the spectrum can help identify the peaks. See "An automatic event detector at the Tonto Forest Seismic Observatory", Blandford, 1974.

1.83 Geographic Data

See geospatial data.

1.84 Geographic Information System (GIS)

A software application designed to capture, store, manipulate, analyze, manage, and present geospatial data.

1.85 Geometric Spreading

The decrease in signal amplitude as a wavefront expands away from its source that accounts for the increasing wavefront size.

1.86 Geospatial Data

Geospatial data is information that identifies the geographic location and characteristics of natural or constructed features and boundaries on the Earth, typically represented by points, lines, polygons and/or complex geographic features, and may contain information attached to a location. Geospatial data is often accessed, manipulated or analyzed through Geographic Information Systems.

1.87 Green's Function

The modeled ground motion at one location produced by a unit force at another location. For moment tensor inversion, for each seismic station it is necessary to calculate Green's functions corresponding to each of the fundamental force couples in the moment tensor.

1.88 GSE 2.1/IMS 1.0 Formats and Protocols

Formats and protocols developed for the Group of Scientific Experts Third Technical Test (GSETT-3) for communication of IMS monitoring data over the internet. The formats and protocols are described in the document Provisional GSE2.1 Message Formats and Protocols from GSETT-3 found at seismo.ethz.ch/prod/autodrm/provisional_GSE2.1.pdf and also in the document Formats and Protocols for Messages IMS1.0 from the International Data Center found at isc.as.uk/standards/isf/download/ims1_0.pdf.

1.89 Historical Data

Waveform and alphanumeric data referenced to times prior to the operational processing time period.

1.90 Hydroacoustic Arrival Group (HAG)

A group of signal detections on different hydrophones from a single hydroacoustic station that have been determined to come from the same event and that can be used to determine azimuth back to the event. HAGs can only be formed for multiple element (array) stations, and hence apply to H stations but not T stations.

1.91 Hydroacoustic Time Domain Measurements

Measurements made directly on waveforms from hydroacoustic sensors, including: signal termination time, signal summation time, signal time spread, signal skewness, signal kurtosis, peak energy in a defined time period, intensity average time in a defined time period, peak energy in a defined time period, and crossing counts (the number of times a waveform crosses a threshold in a defined time period).

1.92 IDC (International Data Center)

The International Data Center (IDC) is the data processing component of the monitoring system associated with the proposed Comprehensive Nuclear Test Ban Treaty (CTBT). The IDC processes the data from a global sensor network known as the IMS. The National Data Centers (NDCs) receive IMS station data and bulletins from the IDC.

1.93 IMS (International Monitoring System)

The International Monitoring System (IMS) is a world-wide network of seismic, hydroacoustic, infrasound, and radionuclide stations deployed as part of the CTBT verification regime.

1.94 Interactive Processing

Analyst directed data processing. Interactive processing can be performed to review and refine existing event hypotheses (automatic or analyst-built) or to build new event hypotheses missed by prior processing.

1.95 IRIS-DMC

The data management center (DMC) run by IRIS (see IRIS). The IRIS-DMC archives and distributes data to support the seismological research community.

1.96 Isotropic Component (of Moment Tensor)

The portion of the moment tensor that represents a purely explosive/implosive source. The moment tensor for an idealized explosion has only an isotropic component.

1.97 Late Signal Association

A network signal association process triggered when a signal detection is made on a waveform after normal network signal association has occurred. Late signal association includes associating the new signal detections to previously formed event hypotheses as well as using them to form new event hypotheses.

1.98 Late-Arriving Waveform

Waveform data acquired by the System after pipeline processing has been initiated.

1.99 Machine Readable Earthquake Data Report

The USGS electronic bulletin format which contains hypocenter parameters, macro-seismic observations and phase and amplitude data. A detailed description can be found at the web site hazards.cr.usgs.gov/weekly/mchedr.txt

1.100 Magnitude Estimation

The process whereby the magnitude (size) of an event is estimated based on the observed waveform characteristics for a specified seismic phase at one or more stations. Magnitude is calculated for each station observing the event (see event magnitude, station) and these results are combined to come up with a network magnitude (see event magnitude, network). The magnitude calculation requires that the location of the event (see event location) be known, so location must be estimated before magnitude. A magnitude estimation calculation formula must account for the decreases in signal amplitude between source and receiver due to geometric spreading and anelastic attenuation. These factors are determined empirically based on the observed amplitudes for a set of events of well-known sizes.

1.101 Magnitude Type

A particular magnitude estimation method based on a specified phase, frequency band, and instrument.

1.102 Master Event Relocation

A method of relative event relocation where the new location is determined relative to an event with a known, fixed location (the master event). The location of the new event is determined by minimizing the travel time differences between the signal detections of the new event and the master event. Assuming the two events are in fact close to each other, this relative location can be determined with significantly greater precision than a standard relocation. However, the location accuracy depends completely on the location accuracy of the master event.

1.103 Maximum Likelihood Magnitude Estimation (MLE)

A method of estimating the magnitude of an event using information from both detecting and non-detecting stations. For the latter, an amplitude measurement is made at the theoretical arrival time of the phase used for the type of magnitude being calculated (see magnitude type), and the assumption is that the amplitude for that phase from the event must be less than or equal to the amplitude measured at the theoretical arrival time.

1.104 Mini-SEED Format

A format used to identify SEED data records without any control header information, also known as Data Only SEED. The Mini-SEED format is described in Appendix G of the SEED Reference Manual from the Incorporated Research Institutions for Seismology (IRIS) found at [fdsn.org/seed_manual/SEEDManual_V2.4.pdf](https://www.fdsn.org/seed_manual/SEEDManual_V2.4.pdf).

1.105 Missed Event

An event that was known to have occurred but that was not detected by the System (automatic processing and/or analyst review). Adjustments can be made to the system to reduce the number of missed events, but usually only with a corresponding increase in the number of false events built by the system.

1.106 Mission Transfer

The process of transferring the execution of System operations from the Primary to the Backup.

1.107 Moment

The amount of energy released by a seismic event. Moment is the scalar size of the moment tensor.

1.108 Moment Tensor

A 3 x 3 matrix of the 9 fundamental force couples that describe the focal mechanism for a particular event. A moment tensor can be decomposed into various components to provide insight into the focal mechanism. The most basic decomposition is into isotropic and deviatoric components.

1.109 Moment Tensor Inversion

The process of determining the values of the force couples in the moment tensor. Moment tensor inversion is based on fitting the observed waveforms at a set of seismic stations with modeled waveforms based on a sum of the properly scaled Green's functions. The scaling factors are the elements of the moment tensor.

1.110 Monitoring Mission Performance

A measure of how well the System is performing the monitoring mission. This is based on the System's metrics and statistics supporting sensor state-of-health, geophysical network capability, algorithmic performance, and detected event statistics.

1.111 Near Real Time

An implication that the delay between a triggering action and response of the system to that action is not significant. Depending on the type and amount of processing required to produce a result, this delay could range from seconds to 30 minutes.

1.112 Network

A group of stations used for monitoring. For example, the IMS network is the group of stations used by the IDC to monitor the CTBT. Spacing between stations in a network is much larger than in an array, and array processing techniques are generally not applied across a network.

1.113 Network Magnitude Detection Threshold

The geographically varying magnitude below which events monitored by a specified network can no longer be detected with a specified level of confidence (generally 90% or 95%). This threshold can either be determined empirically (if a sufficient number of events spanning a range of sizes have occurred in a region) or by modeling.

1.114 Network Processing

Integrated processing of data from two or more stations within a network. If the network processing requires processed station data, then station processing must be completed for all required stations before network processing can begin. Types of network processing include: signal association, event location refinement, and magnitude estimation.

1.115 Noise

Portions of a waveform not containing event information, i.e. without apparent signals.

1.116 Operational Processing Time Period

The time during which analysts may refine and save events without special procedures.

1.117 Operational Subsystem

The portion of the System residing at the principal location that supports the operational mission. This subsystem can serve as Primary or Backup. To insure there is no impact on mission capability, development and testing are supported with separate subsystems (DEV and SUS).

1.118 Operations Log

A log for capturing operational activities, e.g., significant events, station outages, shift changes.

1.119 OPS (Operational Subsystem)

See Operational Subsystem.

1.120 Origin

See event hypothesis location solution.

1.121 Phase

An indication of the path and type of a signal originating from an event traveling through the body of the Earth, the oceans, or the atmosphere. For example the seismic P phase refers to a compressional wave refracting within the mantle of the Earth, while the seismic ScS phase refers to a shear wave reflecting off the outer core boundary.

1.122 Phase Grouping

The process of grouping all of the signal detections from one station that are assumed to come from the same event. Each signal represents a different phase. The system bases grouping on signal detection measurements (e.g. relative timing, azimuth, slowness). Various operations can be made on signal detections after placing them in groups, including phase assignment and creation of a single station event hypothesis.

1.123 Pipeline Processing

The sequence of real-time automatic data processing by the System that begins after acquisition of raw waveform data and results in a set of event hypotheses with associated signal detections.

1.124 Pipeline Transfer

The transfer of pipeline processing from the Primary to the Backup.

1.125 Pixel Family

A group of adjacent time-frequency vs signal attribute values (attributes can be: azimuth, trace velocity, correlation, etc.) created by progressive multi-channel correlation (PMCC) processing of waveform data from an infrasound array. PMCC processing results in spectrogram-type plots (time on the x-axis, frequency on the y-axis, and attributes indicated with a colored pixel), and pixel families represent contiguous regions on the spectrograms. A pixel family is interpreted as indicating the detection of a wave moving across the array.

1.126 PKI (Public Key Infrastructure)

Infrastructure used for the secure exchange of information.

1.127 PKI Credentials

Digital keys used for authenticating messages exchanged between systems.

1.128 Playback

The insertion of a previously captured waveform data acquisition feed in place of the real time raw waveform feed.

1.129 Polarization Features

Features derived from the analysis of three component data (see three component station) that characterize how a signal has been partitioned across the components. Polarization features can be used to identify phase type and for association with an event hypothesis. Polarization features include: azimuth, azimuth uncertainty, slowness, slowness uncertainty, rectilinearity, planarity, horizontal to vertical power ratio, and short and long axis incidence angles.

1.130 Power Detector

A signal detector that triggers on changes in waveform amplitude, which is proportional to power. The most well-known of these is the STA/LTA detector.

1.131 Preliminary Phase Label

A seismic phase label determined using only station signal detection feature measurements, i.e. prior to network signal association. The possible preliminary phase labels are: compressional (P), shear (S), teleseismic (Tx), regional (Rx), and noise (N).

1.132 Primary

The system role defining the location of the active pipeline and analyst processing. May be either OPS or ALT. The Primary is always syncing data to the Backup. During a pipeline transfer, the Primary and Backup roles switch.

1.133 Processing Sequence

An ordered grouping of processing units or other nested processing sequences connected by logic elements that specify sequencing, branching, concurrency, and entry and exit criteria. Processing sequences may specify control parameters such as data buffering and data source, and must adhere to an interface standard for invocation, status return, data access, logging, messaging, etc.

1.134 Processing Stage

A named group of data processing and analysis functions, used to track status of increments of work performed on time intervals and events through the System. The flow of data through the System, from data acquisition, through automated processing and multiple reviews, to reporting of an event, is defined as a series of processing stages (e.g. Pipeline, Analyst 1, etc.). A processing stage may define automatic sequences (see processing sequences), interactive-only activities, or interactive and automatic sequences. A stage description includes: a list of functions that are performed, entry criteria (time, event, or data availability triggers), and exit criteria (completion of processing, recognition of an important event, or declaration by an Analyst).

1.135 Processing Unit

A basic processing action with defined inputs and outputs. Processing units may specify control parameters such as data buffering and data source, and must adhere to an interface standard for invocation, status return, data access, logging, messaging, etc.

1.136 Progressive Multi-Channel Correlation (PMCC)

An array processing technique in which coherency of signals between pairs of sensors within an array is used to detect the presence of a wave propagating across the array. PMCC has proven efficient at detecting low-amplitude, coherent infrasonic signals within incoherent noise. The “progressive” term refers to the idea that the calculation begins with a subnetwork of the array and progressively adds in more distant sensors to confirm the presence of a wave moving across the entire array. The addition of more distant sensors helps to reject false detections that are not coherent across the entire array, reject sensors with poor degraded quality (high local wind noise or sensor issues) and improves the estimation of parameters for true detections. The PMCC processing is performed consecutively in several frequency bands and in adjacent time windows covering the whole period of analysis.

1.137 Q (Quality Factor)

A parameter used to characterize intrinsic attenuation for signals propagating through a particular type of material. Q is inversely proportional to intrinsic attenuation. While strictly speaking Q does not include scattering attenuation, tomographic Q models generally include the effects of both scattering and intrinsic attenuation.

1.138 QC Mask

See waveform QC mask.

1.139 QuakeML

A flexible, extensible and modular XML representation of seismological event data.

1.140 Quality Control (QC)

See waveform quality control.

1.141 Radiation Pattern

A geometric description of the amplitude and direction of motion for the P and S wavefronts near the source.

1.142 Reference Event

An event recognized by an analyst as containing unique or important characteristics that may help in the analysis of future events that are related. For example, a nuclear test could be designated as a reference event for any subsequently detected nearby events thought to be tests.

1.143 Reference Event Database

Data for a collection of reference events, including both parameters and waveforms.

1.144 Regression Testing

Testing of a modified software component that compares current results against past results prior to the modification (for the same inputs) to find unexpected changes (regressions).

1.145 Rejected Event Hypothesis

An event hypothesis determined to be invalid by either the System or an Analyst. The history of rejected event hypotheses, including signal detection associations, are available on the System and rejected event hypotheses can be reopened by Analysts. All signal detections are unassociated from an event hypothesis when it is rejected, making those signal detections available to form other event hypotheses.

1.146 Relative Event Magnitude Estimation

The process of estimating magnitudes (see magnitude estimation) for events in a localized source region by scaling relative to a designated master event with a well-established magnitude.

1.147 Relative Event Relocation

The process of estimating the location of an event hypothesis (see event location) in a localized source region by comparing observations (usually travel times) relative to observations from other nearby reference event hypotheses. Relative event locations calculated in this manner can be more accurate than locations produced by independently relocating the event hypothesis. The process can simultaneously update the locations of all the event hypotheses or just the particular event hypothesis that is being analyzed, if the reference event locations are fixed.

1.148 Remote Operations Center (ROC)

A facility used for short-term data analysis and processing control. The workstations in the ROC allow for remote presentation of displays from either OPS or ALT.

1.149 Rotation

A coordinate system transform that rotates raw channel (see channel, raw) data from a three component station to align the data's axes parallel and perpendicular to a specific azimuth and slowness (i.e. ray path). Rotation produces derived channels corresponding to an arriving signal's radial and transverse ground motion. The purpose of rotation is to enhance the SNR of signals of interest.

1.150 SEED Format

Standard for the Exchange of Earthquake Data (SEED) Format. An international standard format for the exchange of digital seismological data. It was designed for use by the earthquake research community, primarily for the exchange of unprocessed waveform data between institutions. The SEED Format is described in the document SEED Reference Manual from the Incorporated Research Institutions for Seismology (IRIS) found at fdsn.org/seed_manual/SEEDManual_V2.4.pdf

1.151 Sensor Orientation

The orientation of the axis of ground motion recorded by a sensor relative to vertical (inclination) and to geographic North (declination).

1.152 Signal

A portion of a waveform containing information from an event.

1.153 Signal Association

The process of linking (associating) a set of signal detections from a network of stations to an event hypothesis, either existing or new. Association is based on consistency of observed and predicted signal detection feature measurements (e.g. arrival time, azimuth, slowness). Signal association can be done automatically by the system (see pipeline processing), or manually by an analyst.

1.154 Signal Characterization

The process of measuring signal detection features for the purposes of determining the phase of a signal detection, and for determining whether or not a signal detection is consistent with an event hypothesis (see signal association).

1.155 Signal Detection

A specific interval on a waveform marking the arrival of a signal of interest. Other portions of the waveform are noise.

1.156 Signal Detection Feature

A feature associated with a signal detection, e.g. arrival time, back azimuth, horizontal slowness, amplitude, frequency content, etc.

1.157 Signal Detection Feature Measurement

A measurement of a signal detection feature, including measurement uncertainty.

1.158 Signal Detection Feature Prediction

A prediction of a signal detection feature, including prediction uncertainty.

1.159 Signal Detection Template

The set of signal detections across a network of stations that was associated with a reference event. The relative timing of the signal detections is fixed by the location of the reference event, but the absolute timing can be shifted. By shifting the timing, a signal detection template can be superimposed on current waveform data to help determine whether a similar event has occurred and to aid in identifying and associating signal detections.

1.160 Signal Detector Threshold

The threshold that determines when a signal detection will be declared for a given data channel for a given signal detection algorithm.

1.161 Signal Enhancement

Signal processing techniques including filtering (see filter, waveform), beamforming, and three component waveform data rotation used to enhance the signal content and reduce the noise content of waveform data.

1.162 Signal of Interest

An observable signal on a seismic, hydroacoustic, or infrasonic waveform resulting from an event of interest, such as an earthquake or an explosion.

1.163 Single-Station Event Hypothesis

An event hypothesis with associated signal detections coming from only a single station.

1.164 Site

See station.

1.165 Slowness

A measure of the inverse apparent velocity of a wave moving across the surface of the Earth at a station. The inverse of slowness is the apparent velocity of such a wave. Slowness is often used in phase identification and is sometimes used for determining event location.

1.166 Source Type

An assessment of the cause of an event (e.g., deep earthquake, shallow earthquake, explosion, mine collapse). Source type can be determined automatically or by an analyst.

1.167 Source Type Plot

A plot used to differentiate different types of seismic sources based on their moment tensor decompositions. The coordinates of a source type plot are based on parameters derived from the relative size of the moment tensor components.

1.168 STA/LTA

A signal detection method that is based on a sudden change in signal power resulting from the onset of a signal. STA/LTA is calculated as a ratio of short-term average (STA) signal power (or energy) to a long-term average (LTA) power (or energy). The STA time window typically precedes the LTA time window. When there is no signal present, hence only noise in both windows, the STA/LTA ratio is ~ 1 . When a signal is present in the STA time window and noise is present in the LTA time window, the STA/LTA ratio is > 1 . A detection is declared when the STA/LTA ratio exceeds a specified threshold.

1.169 Standalone Subsystem

A distribution of the System containing a selected set of system components, not connected to other subsystems, used for standalone analysis and site surveys.

1.170 Station

An installation where monitoring sensors are installed. Multiple sensors can be installed at the same station (see channel). An array is a group of stations, but is sometimes referred to as a station.

1.171 Station Data

Data sent to the System by contributing stations. This includes both the ground-motion data (see waveform) as well as state-of-health (SOH) station data.

1.172 Station Magnitude

See event magnitude, station.

1.173 Station Magnitude Detection Threshold

The geographically-varying event magnitude below which a station is not expected to detect events. This can be empirically estimated as the magnitude at which a station's signal detections no longer follow the Gutenberg & Richter frequency-magnitude relationship predicting that for every decrease in size of 1 magnitude unit the number of events detected should increase by a factor of 10. The highest magnitude at which a station's detected events deviate from this prediction indicates the threshold below which the station does not detect events presumed to have occurred.

1.174 Station Processing

Processing of data from a station that is independent of processing of data from any other stations. Types of station processing include: waveform quality control, waveform filtering (see filter, waveform), beamforming, signal detection, signal characterization, and phase grouping.

1.175 Station State-Of-Health (SOH)

An assessment of how well a station is functioning for a specified time interval. Station SOH is based on station SOH data, which may include any type of data that can be time indexed and that can be used to determine the capability of a station to meet mission requirements. E.g., status of sensor channels, site temperature, power status, security status, etc.

1.176 Storage Format

A collection of database table descriptions, waveform file formats, and parameter file formats that are used to store the data used by the System and are documented in the Database Design Document (DBDD).

1.177 Subspace Detector

A special class of waveform correlation signal detector (see waveform correlation event processing) in which the incoming data is compared against a suite of similar template waveforms (i.e. a subspace) rather than a single template waveform. The comparison is to a linear combination of the separate waveforms; the weights for each are determined dynamically as part of the detection processing to achieve the best composite match. Using a subspace detector instead of a single template can make the correlation more robust to differences in source mechanism or source location.

1.178 Swarm Sequence

A sudden increase in seismic activity within a focused area that is not associated with a mainshock (i.e. not an aftershock sequence). As with an aftershock sequence, the source mechanisms of the events within a swarm tend to be very similar, reflecting the underlying cause. Swarms are often associated with volcanic phenomena – e.g. the upward movement of magma from deep in the Earth before an eruption – and may be monitored to track potential hazards.

1.179 System Backup

The archiving of data, files, software, etc., required to restore the System to a previous state.

1.180 System Configuration

The complete set of system parameters that define the operation of the System software. Examples include sensor thresholds, filters (see filter, waveform), the particular version of an earth model in use, and processing sequences. Each instance of a system configuration is saved so the state of all parameters at any time can be recalled.

1.181 System Message

A message generated on the System and distributed to system users. System messaging is controlled by setting various parameters including level (failure, warning, notification), target (intended recipient), and triggering criteria.

1.182 System Performance

The overall performance of the system as measured by CPU usage, disk space usage, system up-time, network usage, and status of software processes.

1.183 System Restore

The restoration of the System to a previous state (see system backup).

1.184 System Storage Format

A collection of database table descriptions, waveform file formats, and parameter file formats that are used to store the data used by the System and are documented in the Database Design Document.

1.185 Test Data Set

A group of artifacts that comprise the required components to define a single test. This group contains a test name, a list of the station(s) associated with the waveform data to be used for replay, the replay start and stop time for the waveform data, the System state start time (the state start time is prior to the replay start time) to allow the System to establish a System state baseline enabling consistent replay test runs, and optionally a set of calibrated test results (this set can include expected number of bulletins, detections, etc. to be constructed during the replay test).

1.186 Three Component Station

A seismic station with separate instruments measuring ground motion in three perpendicular directions: up-down, north-south, and east-west. These directions are often referred to as Z, N, E. Also referred to as a 3C station.

1.187 Time Domain Measurements

Measurements made directly on time-series data, i.e., waveforms. Examples of general time domain measurements include onset time, amplitude, and period.

1.188 Training Data Set

Raw waveforms (see waveform, raw) and alphanumeric data (processing results) for a specific time period that provide a good selection of known events suitable for analyst training.

1.189 Training Subsystem

A subset of the event analysis portion of the System that is used to interactively teach analysts how to perform the mission.

1.190 Unit Testing

A method by which individual units of source code (sets of one or more computer program modules together with associated control data, usage procedures, and operating procedures) are tested to determine if they are fit for use. (definition from Wikipedia).

1.191 Virtual Event Hypothesis

A trial event hypothesis created for analyzing waveform and alphanumeric data in an attempt to discover evidence supporting the existence of an actual event.

1.192 Virtual Origin

See virtual event hypothesis.

1.193 Waveform

A generic term for either a raw waveform (see waveform, raw) or a derived waveform (see waveform, derived).

1.194 Waveform Correlation Event Processing

A technique used to find events by matching current waveforms to waveforms of known historical events. Waveform similarity is determined using the correlation coefficient. When a match is found, there is high probability that a new event has occurred that is of the same source type and near the same location (see event location) as the historical event.

1.195 Waveform Processing

Any operation on waveform data involving signal detection (see signal detection algorithms), polarization measurements (see polarization features), time domain measurements, frequency domain measurements, beamforming, magnitude measurements (see magnitude estimation), filtering (see filter, waveform), waveform correlation (see waveform correlation event processing), and ambient noise calculations.

1.196 Waveform QC Mask

The tag applied to a segment of waveform data with a QC (see quality control) problem. Each QC mask includes a start and stop time and a description of the type of problem. Subsequent waveform processing algorithms may use this information to mask (i.e. ignore) these segments.

1.197 Waveform Quality Control

The processing of waveform data to identify problems related to data acquisition and/or transfer (e.g. dropouts, spikes, etc.). In particular waveform quality control is focused on identifying problems that can lead to false signal detections and/or to missed true signal detections.

1.198 Waveform, Derived

Output from a derived channel (see channel, derived) during a particular time interval. E.g. a bandpass filtered version of a raw waveform (see waveform, raw); a beam created by summing multiple raw waveforms from the elements of an array.

1.199 Waveform, Raw

Output from a raw channel (see channel, raw) during a particular time interval.



Sandia National Laboratories